



Expert Opin Environ Biol 2018, Volume: 7 DOI: 10.4172/2325-9655-C2-024

International Conference on

BIOFUELS & BIOENERGY

July 16-17, 2018 | Madrid, Spain

Wastewater treatment and CO₂ sequestration with simultaneous generation of bioelectricity, volatile fatty acids and bioalgal lipids using algal assisted microbial fuel cells (AAMFC)

Muluken Eshetu Tefera Jimma University, Ethiopia

n this study, biodiesel, bioethanol and briquette samples were sequentially produced from spent coffee ground. The oil extracted from spent coffee ground with solvent extraction route at hexane to spent coffee ground ratio of 22.5g/g with an extraction time of 30.4min resulting in 11.892% of oil yield. This was comparable with literature values and subsequently used for biodiesel production experiments using a 1% by wt of NaOH at reaction temperatures and residence times ranging from 50 to 65 °C and 20 to 60min, respectively. The optimization carried out using central composite design methodology gave 81.507% of methyl-ester yield at a reaction temperature of 57.133 °C and reaction time (residence time) of 45.117 min with model determination coefficient (R2) of 0.9465 while the optimum reducing sugar yield for dilute acid hydrolysis experiments for ranges of operating parameters of temperature (70-100 °C) and (1-3M)of H²SO⁴ concentrations was found to

be 39.161% at a temperature of 98.313°C and H²SO⁴ acid concentration of 2.962M. Experiments were conducted at the predicted optimum conditions and resulted 79.65% of biodiesel yield (out of 11.892g of oil) and reducing sugars yield of 37.28 %(out of the hydrolysate). The bio ethanol produced by simple distillation having alcohol by volume yield of 55% can be considered as a good result and it can be easily concentrated to a fuel grade ethanol by using fractionating column. Moreover, the characteristics of the biodiesel produced were in good agreement with ASTM and EN standards. The end product of the process; briquette has been produced from 75% wt of dilute acid hydrolysis residue and 25% wt of glycerol, resulted a calorific value of 13.35MJ/kg, with its easy mold -ability. This study signifies the value addition that can be affected from spent coffee ground and results obtained in this regard are discussed.

mulushakached@gmail.com